Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Wiz

Supplier's address: WiZ, WiZ I.B.R.S. / C.C.R.I. Number 10461, 5600VB Eindhoven, NL

Model identifier: 9290024487AW

Type of light source:

Lighting to shoology used	LFD	Non-directional or	NDLS
Lighting technology used:	LED		NDL3
		directional:	
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light	Yes
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with
			specific dimmers

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumpt mode (kWh/1000 up to the nearest i	h), rounded	5	Energy efficiency class	F		
Useful luminous indicating if it refe in a sphere (360 cone (120 ^o) or in a (90 ^o)	rs to the flux ?), in a wide	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500		
On-mode pow expressed in W	ver (P _{on}),	4,9	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50		
Networked standb for CLS, expresse rounded to the sec	d in W and	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90		
Outer H	eight	116	Spectral power	See image		
dimensions W	/idth	39	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	39	range 250 nm to 800 nm, at full-load				
Claim of equival	ent power ^(a)	Yes	lf yes, equivalent power (W)	40			
			Chromaticity coordinates (x and y)	0,458 0,410			
Parameters for LED and OLED light sources:							
R9 colour rende	ring index value	0	Survival factor	0,90			
the lumen main	tenance factor	0,93					
Parameters for	LED and OLED ma	ains light sources:					
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
source replaces	an LED light a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	_			
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-' : not applicable;

(b)'-' : not applicable;

